Existing Conditions


Illustration	Mitigation Description	Existing (2013)
₹\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Existing Geometrics	√
711/	NB Right-turn lane on MLK	
1117	SB right-turn lane on MLK	
7111 <i>/</i>	3rd NB through lane on MLK, requiring a 3rd receiving lane on MLK north of Estes	
711 <i>//</i>	2nd SB left-turn lane on MLK, requiring a 2nd receiving lane on Estes east of MLK	
	2nd EB and WB through lanes on Estes, requiring 2nd receiving lanes on Estes both east and west of MLK	
	2nd WB left-turn lane on Estes	
1 #	2nd EB left-turn lane on Estes	




	I
Level of Service	Description
A	Minimal Delays, avg. delay is less than 10 seconds
В	Low levels of Delay and Queuing; avg. delay is between 10 and 20 seconds
С	Intermittently vehicles wait through more than one signal cycle, occasionally back ups may occur but traffic flow is stable; avg. delay is between 20 and 35 seconds.
D	Delays at intersections may become extensive, but enough cycles with lower demand occur to permit peri- odic clearance, preventing excessive backups; avg. de- lay is between 35 and 55 seconds
E	Traffic fills intersection capacity and long queues and delays are to be expected and many vehicles will wait for more than one signal cycle; avg. delay is between 55 and 80 seconds
F	Traffic demand exceeds capacity of intersection resulting in very long queues and delays for most vehicles. Most vehicles at the intersection will need to wait through more than one signal cycle; avg delay exceeds 80 seconds



Option A 1





LAND (JSES			. 1		DAILY TR	RIPS
687	Resid	. Units	>	>	->	4,592	
93,700	Office	e sf'	>	>	->	1,034	ļ
93,350	Retai	l sf'	>	>	->	3,027	•
13000	Comr	mercial sf	>	>	->	836	
59300	Hotel	sf'	>	>	->	484	
30 000	Inctit	utional sf		>	.	988	
30,000	mstit	utionat 3i	1		<u> </u>	366	
30,000		0,961 to	↓				
J			↓				ļ
F			↓				l

- Mitigation
 Measure Identified in Carolina North TIA
 - Improvement required to mitigate background growth and CN traffic.

WITHOUT mitigation


Estes Drive & M.L.K. Jr.		Build (2023) A1				
		А	AM		М	
Control	Approach	LOS	Delay	LOS	Delay	
	Total	E	67.4	F	92.9	
	Eastbound	F	82.5	F	131.4	
Signalized	Westbound	Е	66.9	F	105.2	
	Northbound	D	46.7	F	84.5	
	Southbound	Е	68.6	Е	75.6	

WITH mitigation

Estes Drive & M.L.K. Jr.		Build (2023) A1				
		AM		PM		
Control	Approach	LOS	LOS Delay		Delay	
	Total	D	46.2	D	50.9	
	Eastbound	Е	66.4	Е	61.1	
Signalized	Westbound	Е	58.5	Е	59.7	
	Northbound	С	30.3	D	48.0	
	Southbound	D	36.9	D	42.9	







LAND US	SES	CW Plan	DAILY TRIPS		
620	Resid. Units	>	4,003		
100,000	Office sf'	>	1,152		
25,000	Retail sf'		761		
30,000	Commercial sf'	>	1927		
65,000	Hotel sf'	>>	531		
50,000	Institutional sf'	>	1,600		
♦ 9,972 total daily trips					

*	Mitigation
^	Measure Iden-
	tified in Caro-
	lina North TIA

Improvement required to mitigate background growth and CN traffic.

WITHOUT mitigation

Estes Drive & M.L.K. Jr.		Central West Plan			
		А	M	PM	
Control	Approach	LOS	Delay	LOS	Delay
Signalized	Total	Е	58.3	F	91.5
	Eastbound Westbound	F	81.2	F	126.6
	Northbound	Е	68.5	F	103.5
	Southbound	D	40.1	F	84.3

VVIIII IIIIII dulloli			
es Drive & M.L.K. Jr.	Central West Plan		
les Diive & M.L.K. Ji.			

Estes Drive & M.L.K. Jr.						
Estes brive & M.E.R. jr.		AM		PM		
Control	Approach	LOS Delay		LOS	Delay	
ignalized	Total	D	46.6	D	49.9	
	Eastbound Westbound	Е	67.0	Е	65.0	
	Northbound	Е	55.4	D	53.8	
	Southbound	С	28.5	D	45.8	

