


- CONSTRUCTION NOTES:
1. CLEAR THE ENTRANCE AND EXIT AREA OF ALL VEGETATION, ROOTS, AND OTHER OBJECTIONABLE MATERIAL AND PROPERLY GRADE IT.
 2. PLACE THE GRAVEL TO THE SPECIFIC GRADE AND DIMENSIONS SHOWN ON THE PLANS, AND SMOOTH IT.
 3. PROVIDE DRAINAGE TO CARRY WATER TO A SEDIMENT TRAP OR OTHER SUITABLE OUTLET.
 4. USE GEOTEXTILE FABRICS IN ORDER TO IMPROVE STABILITY OF THE FOUNDATION.
 5. INSTALL SILT FENCE, TREE PROTECTION FENCE OR CONSTRUCTION FENCE BETWEEN EDGE OF DISTURBED AREAS AND EXISTING ROADWAY TO ENSURE CONSTRUCTION ENTRANCE IS USED.
 6. IF CONSTRUCTION ON THE SITE IS OF SUCH NATURE THAT SUFFICIENT MUD IS NOT REMOVED FROM THE VEHICLE TRAVELING OVER THE STONE, THEN THE TIRES OF VEHICLES LEAVING THE SITE MUST BE WASHED BEFORE ENTERING THE PUBLIC ROAD.

- MAINTENANCE NOTES:
1. INSPECT ALL MEASURES AT LEAST WEEKLY AND AFTER EACH RAINFALL OF 1.0 INCH OR GREATER. MAKE ANY REQUIRED REPAIRS IMMEDIATELY.
 2. MAINTAIN THE GRAVEL PAD IN A CONDITION TO PREVENT MUD OR SEDIMENT FROM LEAVING THE CONSTRUCTION SITE. THIS MAY REQUIRE PERIODIC TOPDRESSING WITH 2-INCH STONE.
 3. SEDIMENT ON ROADWAYS IS TO BE REMOVED IMMEDIATELY BY BROOM AND SHOVEL, EITHER BY MANUAL OR MECHANICAL MEANS, AND NOT TO BE WASHED OFF WHERE IT HAS THE POTENTIAL TO ENTER A STREAM, DRAINAGE WAY OR STORM DRAIN SYSTEM.

" NOT TO SCALE "

	TOWN OF CHAPEL HILL STANDARD DETAIL	
	REVISIONS 05/2024	COMMERCIAL CONSTRUCTION ENTRANCE
DATE: 02/2017	EC-1.01	