



GENERAL NOTES:

1. REGARDLESS OF AGE, ALL ACCESSIBLE SPACES SHALL BE IDENTIFIED BY ABOVE-GROUND SIGNS ONLY.
2. NEW SPACES SHALL NOT USE GROUND-PAINTED SYMBOLS.
3. ACCESSIBLE SPACES ARE REQUIRED TO BE STRIPED OFF ONLY; BLUE COLORING IS NOT NECESSARY NOR REQUIRED.
4. STRIPING IS WHITE ON DARK PAVEMENT; BLACK ON LIGHT PAVEMENT. (N.C.D.O.T.)
5. IF PEDESTRIAN TRAFFIC IS ANTICIPATED BETWEEN ACCESSIBLE PARKING SPACE AND PARKING SIGNAGE, MINIMUM HEIGHT OF SIGNAGE SHALL BE 7-FT.
6. SIGNS SHALL BE MOUNTED ON ALUMINUM OR GALVANIZED STEEL POST. POST SHALL BE EITHER 2" SQUARE OR 2" WIDE (MIN.) U-CHANNEL (1" CHANNEL DEPTH MIN.)
7. USE ISOLATION WASHERS IF BOLTS ARE DISSIMILAR METAL THAN SIGN POST. ISOLATION WASHERS SHALL BE MADE OF PHOTODEGRADATION-RESISTANT MATERIAL, SUCH AS BLACK NEOPRENE, EPDM OR HDPE.

" NOT TO SCALE "



TOWN OF CHAPEL HILL
STANDARD DETAIL

REVISIONS

05/2024

ACCESSIBLE
PARKING SIGNAGE

02/2017

T-2.07